Product End of Life Instructions

TeSys Deca thermal overload relays 48-65 A-class 10A





S End of Life Instructions



Recommendation	Number on drawing	Component / Material	Weight (in g)	Comment
To be depolluted	1,4,5	PC, ABS-PC, PA, PA6, HDPE, SAN with brominates flame retardants	105.076	
To be depolluted	2,3	Other plastic parts with brominates flame retardants	0.51	

Product description

Manufacturer identification	Schneider Electric Industries SAS
Brand name	Schneider Electric
Product function	The main purpose of the thermal overload relays is to detect overload currents in order to protect the motor.
Product reference	LRD365
Total representative product mass	375 g
Representative product dimensions	70mm x 55mm x 123mm
Accessories	No
Date of information release	08/2022

Additional information

Legal information	and Elec legislation facilities	This product family is in the scope of European Union directive 2012/19/EU on Waste Electrical and Electronic Equipment (WEEE). The product family must be disposed according to the legislation of the country. This document is intended for use by end of life recyclers or treatment facilities. It provides the basic information to assure an appropriate end of life treatment for the components and materials of the product.		
In case of special transportation: transportation method	Νο			
Recyclability potential	75%	Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).		

Schneider Electric Industries SAS Country Customer Care Center http://www.schneider-electric.com/contact 35, rue Joseph Monier CS 30323 F- 92506 Rueil Malmaison Cedex RCS Nanterre 954 503 439 Capital social 896 313 776 €

www.schneider-electric.com

ENVEOLI0804005_V2

Published by Schneider Electric © 2019 - Schneider Electric – All rights reserved

08/2022