



# Ledinaire All-in floodlights

## BVP167 LED12/830\_40\_65 DOB 10W SWB

Ledinaire All-in floodlights, 10 W, 1100 lm, 1200 lm, 3000 K, 4000 K, 6500 K, Symmetrical

With this Ledinaire all-in floodlights range, you can easily adjust the color temperature by a simple switch. No need to choose between warm white, neutral white or cool white anymore, you get all this in one single product ! The range comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

### Product data

| General Information                |                                          |
|------------------------------------|------------------------------------------|
| Lamp family code                   | LED12S [LED module, system flux 1200 lm] |
| Number of gear units               | 1 unit                                   |
| Driver included                    | Yes                                      |
| Photocell                          | -                                        |
| Light source engine type           | LED system in flux                       |
| Value ladder                       | Value                                    |
| Embedded control                   | -                                        |
| Light Technical                    |                                          |
| Upward light output ratio          | 0                                        |
| Luminous Flux                      | 1,100 1,200 lm                           |
| Standard tilt angle posttop        | 27°                                      |
| Standard tilt angle side entry     | -                                        |
| Luminous Efficacy (rated) (Nom)    | 110 120 lm/W                             |
| Correlated Color Temperature (Nom) | 3000 4000 6500 K                         |

| Color rendering index (CRI)                                     | 80                                   |
|-----------------------------------------------------------------|--------------------------------------|
| Flickering value (PstLM) - Flickering value as per EN 61000-3-3 | 1                                    |
| Light source color                                              | 830 warm white and 865 cool daylight |
| Optic type                                                      | Symmetric 110°                       |
| Optical cover type                                              | Glass                                |
| Luminaire light beam spread                                     | 110°                                 |
| Optic type outdoor                                              | Symmetrical                          |
| All-in Type                                                     | All-in, Multi Color Temperature      |
| Operating and Electrical                                        |                                      |
| Input Voltage                                                   | 220-240 V                            |
| Line Frequency                                                  | 50 or 60 Hz                          |
| Inrush current                                                  | 0.78 A                               |
| Inrush time                                                     | 0.00648 ms                           |
| Power Consumption                                               | 10 W                                 |

Ledinaire All-in floodlights

|                                          |                          |
|------------------------------------------|--------------------------|
| Power Factor (Fraction)                  | 0.95                     |
| Connection                               | Flying leads/wires       |
| Cable                                    | Cable 1.0 m without plug |
| Number of products on MCB of 16 A type B | 218                      |

Temperature

|                           |               |
|---------------------------|---------------|
| Ambient temperature range | -25 to +40 °C |
|---------------------------|---------------|

Controls and Dimming

|                               |                                      |
|-------------------------------|--------------------------------------|
| Dimmable                      | No                                   |
| Driver/power unit/transformer | Driver integrated on LED board (DoB) |
| Control interface             | -                                    |
| Constant light output         | No                                   |

Mechanical and Housing

|                                     |                                                                  |
|-------------------------------------|------------------------------------------------------------------|
| Housing Material                    | Aluminum die cast                                                |
| Reflector material                  | Polycarbonate                                                    |
| Optic material                      | Glass                                                            |
| Optical cover material              | Tempered glass                                                   |
| Fixation material                   | Steel                                                            |
| Housing Color                       | RAL 7043                                                         |
| Mounting device                     | Via U Shaped Bracket, Aiming Scale Angle, Universal Installation |
| Optical cover shape                 | Flat                                                             |
| Optical cover finish                | Clear                                                            |
| Overall length                      | 130 mm                                                           |
| Overall width                       | 85 mm                                                            |
| Overall height                      | 31 mm                                                            |
| Effective projected area            | 0.006300000000000001 m²                                          |
| Dimensions (Height x Width x Depth) | 31 x 85 x 130 mm                                                 |

Approval and Application

|                                        |                                              |
|----------------------------------------|----------------------------------------------|
| Ingress protection code                | IP65 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code           | IK07 [2 J reinforced]                        |
| Surge Protection (Common/Differential) | 1.5/1.5 kV                                   |
| Sustainability rating                  | -                                            |
| Protection class IEC                   | Safety class I                               |
| Glow-wire test                         | Temperature 650 °C, duration 30 s            |

|                                    |                                                |
|------------------------------------|------------------------------------------------|
| Flammability mark                  | For mounting on normally flammable surfaces    |
| CE mark                            | CE mark                                        |
| ENEC mark                          | -                                              |
| Warranty period                    | 5 years                                        |
| Photobiological risk               | Photobiological risk group 1 @200mm to EN62778 |
| Photobiological risk specification | 0.2 m                                          |
| EU RoHS compliant                  | Yes                                            |

Initial Performance (IEC Compliant)

|                                       |                                                       |
|---------------------------------------|-------------------------------------------------------|
| Luminous flux tolerance               | +/-10%                                                |
| Initial chromaticity                  | (0.440,0.403); (0.369,0.364); (0.313,0.337)<br>SDCM<5 |
| Power consumption tolerance           | +/-10%                                                |
| Init. Color Rendering Index Tolerance | -2                                                    |

Over Time Performance (IEC Compliant)

|                                                         |       |
|---------------------------------------------------------|-------|
| Control gear failure rate at median useful life 50000 h | 7.5 % |
| Lumen maintenance at median useful life* 50000 h        | 80    |

Application Conditions

|                                    |                |
|------------------------------------|----------------|
| Performance ambient temperature Tq | 25 °C          |
| Suitable for random switching      | Not applicable |

Product Data

|                                 |                                    |
|---------------------------------|------------------------------------|
| Order product name              | BVP167 LED12/830_40_65 DOB 10W SWB |
| Full product name               | BVP167 LED12/830_40_65 DOB 10W SWB |
| Full product code               | 872016973601699                    |
| Order code                      | 911401871386                       |
| Material Nr. (12NC)             | 911401871386                       |
| Numerator - Quantity Per Pack   | 1                                  |
| Net Weight (Piece)              | 0.250 kg                           |
| EAN/UPC - Product/Case          | 8720169736016                      |
| Numerator - Packs per outer box | 24                                 |
| EAN/UPC - Case                  | 8720169736207                      |

Ledinaire All-in floodlights

Dimensional drawing

