

## Fuse - FUSE 10,3X38 15A PV A - 3062784

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse, for the photovoltaics industry according to UL 2579, length: 38 mm, diameter: 10.3 mm, color: white

### Your advantages

- ✓ Use in PV lines with a nominal voltage of up to 1000 V DC
- ✓ Designed in accordance with the photovoltaic standard UL 2579
- ✓ 10x38 midget fuses for reliable protection of PV modules and their control system



### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 10 pc                                                                                                   |
| GTIN         | <br>4 046356 768221 |
| GTIN         | 4046356768221                                                                                           |

### Technical data

#### General

|       |       |
|-------|-------|
| Color | white |
|-------|-------|

#### Dimensions

|          |         |
|----------|---------|
| Length   | 38 mm   |
| Diameter | 10.3 mm |

#### General

|      |                    |
|------|--------------------|
| Fuse | Midget / 10.3 x 38 |
|------|--------------------|

#### Ambient conditions

|                                          |                                                                        |
|------------------------------------------|------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 85 °C                                                       |
| Ambient temperature (storage/transport)  | -25 °C ... 55 °C (For a short time, not exceeding 24 h, -60 to +70 °C) |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                          |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                        |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                        |

## Fuse - FUSE 10,3X38 15A PV A - 3062784

### Technical data

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27142002 |
| eCl@ss 11.0   | 27142002 |
| eCl@ss 4.0    | 27142000 |
| eCl@ss 4.1    | 27142000 |
| eCl@ss 5.0    | 27142000 |
| eCl@ss 5.1    | 27142000 |
| eCl@ss 6.0    | 27142000 |
| eCl@ss 7.0    | 27142002 |
| eCl@ss 8.0    | 27142002 |
| eCl@ss 9.0    | 27142002 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000035 |
| ETIM 4.0 | EC002704 |
| ETIM 5.0 | EC000035 |
| ETIM 6.0 | EC002704 |
| ETIM 7.0 | EC002704 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211915 |
| UNSPSC 7.0901 | 39121514 |
| UNSPSC 11     | 39121514 |
| UNSPSC 12.01  | 39121514 |
| UNSPSC 13.2   | 39121627 |
| UNSPSC 18.0   | 39121627 |
| UNSPSC 19.0   | 39121627 |
| UNSPSC 20.0   | 39121627 |
| UNSPSC 21.0   | 39121627 |

### Approvals

#### Approvals

Approvals

EAC / UL Listed

## Fuse - FUSE 10,3X38 15A PV A - 3062784

### Approvals

Ex Approvals

### Approval details

|                    |                                                                                   |                                                                                                                                                       |         |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| EAC                |  | RU C-<br>DE.BL08.B.00724                                                                                                                              |         |
| UL Listed          |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E360477 |
| Nominal voltage UN |                                                                                   | 1000 V                                                                                                                                                |         |

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>