

# Specyfikacje



Zdjęcie jest reprezentatywne

## Eaton 111978

Eaton Moeller series Power Defense - Molded Case Circuit Breaker. Circuit-breaker, 3 p, 800A

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series Power Defense molded case circuit-breaker
<b>CATALOG NUMBER</b>	111978
<b>EAN</b>	4015081115266
<b>PRODUCT LENGTH/DEPTH</b>	401 mm
<b>PRODUCT HEIGHT</b>	207 mm
<b>PRODUCT WIDTH</b>	210 mm
<b>PRODUCT WEIGHT</b>	19 kg
<b>COMPLIANCES</b>	RoHS conform
<b>CERTIFICATIONS</b>	IEC VDE 0660 IEC/EN 60947
<b>MODEL CODE</b>	LZMN4-AE800-I



Powering Business Worldwide

## Delivery program

<b>CIRCUIT BREAKER FRAME TYPE</b>	LZM4
<b>APPLICATION</b>	Use in unearthed supply systems at 525 V
<b>AMPERAGE RATING</b>	800 A
<b>NUMBER OF POLES</b>	Three-pole

## Technical data - electrical

<b>VOLTAGE RATING</b>	690 V - 690 V
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT AUXILIARY CONTACTS</b>	6000 V
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT MAIN CONTACTS</b>	8000 V
<b>RATED OPERATIONAL CURRENT</b>	2000 A (380/400 V AC-1, making and breaking capacity) 800 A (415 V AC-3, making and breaking capacity) 2000 A (690 V AC -1, making and breaking capacity) 1600 A (415 V AC-1, making and breaking capacity) 800 A (660-690 V AC-3, making and breaking capacity)
<b>RATED SHORT-TIME WITHSTAND CURRENT (T = 0.3 S)</b>	19.2 kA
<b>RATED SHORT-TIME WITHSTAND CURRENT (T = 1 S)</b>	19.2 kA
<b>INSTANTANEOUS CURRENT SETTING (II) - MIN</b>	1600 A
<b>INSTANTANEOUS CURRENT SETTING (II) - MAX</b>	9600 A
<b>OVERLOAD CURRENT SETTING (IR) - MIN</b>	400 A
<b>OVERLOAD CURRENT SETTING (IR) - MAX</b>	800 A
<b>SHORT DELAY CURRENT SETTING (ISD) - MIN</b>	0 A
<b>SHORT DELAY CURRENT SETTING (ISD) - MAX</b>	0 A
<b>SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MIN</b>	1600 A
<b>SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MAX</b>	9600 A

<b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 HZ</b>	37 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 HZ</b>	37 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 440 V, 50/60 HZ</b>	26 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 525 V, 50/60 HZ</b>	19 kA
<b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 240 V, 50/60 HZ</b>	105 kA
<b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 400/415 V, 50/60 HZ</b>	105 kA
<b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 440 V, 50/60 HZ</b>	74 kA
<b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 525 V, 50/60 HZ</b>	53 kA
<b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 690 V, 50/60 HZ</b>	40 kA
<b>SHORT-CIRCUIT TOTAL BREAKTIME</b>	< 25 ms ( ≤ 415 V); < 35 ms ( > 415 V)
<b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>	Screw connection
<b>ISOLATION</b>	500 V AC (between auxiliary contacts and main contacts) 300 V AC (between the auxiliary contacts)
<b>OVERVOLTAGE CATEGORY</b>	III
<b>UTILIZATION CATEGORY</b>	B (2000A: A, IEC/EN 60947- 2)
<b>POLLUTION DEGREE</b>	3
<b>LIFESPAN, ELECTRICAL</b>	2000 operations at 400 V AC-3 2000 operations at 415 V AC-3

1000 operations at 690 V  
AC-3  
2000 operations at 690 V  
AC-1  
3000 operations at 400 V  
AC-1  
3000 operations at 415 V  
AC-1

## Technical data - mechanical

<b>TYPE</b>	Circuit breaker
<b>RELEASE SYSTEM</b>	Electronic release
<b>MOUNTING METHOD</b>	Fixed Built-in device fixed built-in technique
<b>DEGREE OF PROTECTION</b>	In the area of the HMI devices: IP20 (basic protection type) IP20
<b>DEGREE OF PROTECTION (IP), FRONT SIDE</b>	IP40 (with insulating surround) IP66 (with door coupling rotary handle)
<b>DEGREE OF PROTECTION (TERMINATIONS)</b>	IP10 (tunnel terminal) IP00 (terminations, phase isolator and band terminal)
<b>PROTECTION AGAINST DIRECT CONTACT</b>	Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
<b>SHOCK RESISTANCE</b>	15 g (half-sinusoidal shock 11 ms)
<b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b>	0
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>	0
<b>NUMBER OF OPERATIONS PER HOUR - MAX</b>	60
<b>HANDLE TYPE</b>	Rocker lever
<b>POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT</b>	Front side
<b>DIRECTION OF INCOMING SUPPLY</b>	As required
<b>STANDARD TERMINALS</b>	Screw terminal
<b>TERMINAL CAPACITY (CONTROL CABLE)</b>	0.75 mm <sup>2</sup> - 1.5 mm <sup>2</sup> (2x) 0.75 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (1x)
<b>TERMINAL CAPACITY (COPPER BUSBAR)</b>	M10 at rear-side screw connection Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate

## Design verification as per IEC/EN 61439 - technical data

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	800 A
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	111.36 W

	<p>Min. 25 mm x 5 mm at rear-side 1-hole module plate</p> <p>Min. 25 mm x 5 mm direct at switch rear-side connection</p> <p>Max. 50 mm x 10 mm (2x) direct at switch rear-side connection</p> <p>Max. 80 mm x 10 mm (2x) direct at switch rear-side connection</p> <p>50 mm x 10 mm (2x) at rear-side 2-hole module plate</p> <p>Max. 80 mm x 10 mm (2x) at rear-side width extension</p> <p>Min. 60 mm x 10 mm at rear-side width extension</p>
<b>TERMINAL CAPACITY (COPPER SOLID CONDUCTOR/CABLE)</b>	<p>50 mm<sup>2</sup> - 240 mm<sup>2</sup> (4x) at 4-hole tunnel terminal</p> <p>35 mm<sup>2</sup> - 185 mm<sup>2</sup> (4x) at rear-side 2-hole module plate</p> <p>120 mm<sup>2</sup> - 300 mm<sup>2</sup> (1x) at rear-side 1-hole module plate</p> <p>95 mm<sup>2</sup> - 300 mm<sup>2</sup> (2x) at rear-side 1-hole module plate</p> <p>95 mm<sup>2</sup> - 240 mm<sup>2</sup> (6x) at rear-side width extension</p> <p>300 mm<sup>2</sup> (4x) at rear-side width extension</p> <p>95 mm<sup>2</sup> - 185 mm<sup>2</sup> (2x) at rear-side 2-hole module plate</p>
<b>TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE)</b>	<p>120 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) direct at switch rear-side connection</p> <p>50 mm<sup>2</sup> - 185 mm<sup>2</sup> (4x) direct at switch rear-side connection</p>
<b>TERMINAL CAPACITY (COPPER STRIP)</b>	<p>10 segments of 80 mm x 1 mm (2x) at rear-side width extension</p> <p>Min. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched)</p> <p>Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal</p> <p>10 segments of 50 mm x 1</p>

---

mm (2x) at 1-hole module  
plate  
Max. 10 segments of 32  
mm x 1 mm (2x) at flat  
conductor terminal  
Max. 10 segments of 50  
mm x 1 mm (2x) at rear-  
side connection (punched)

---

**CLIMATIC PROOFING**

Damp heat, cyclic, to IEC  
60068-2-30  
Damp heat, constant, to  
IEC 60068-2-78

---

**LIFESPAN, MECHANICAL**

10000 operations

---

## Design verification as per IEC/EN 61439

<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF</b>	Is the panel builder's responsibility.

## Additional information

<b>FEATURES</b>	Protection unit Motor drive optional
<b>FUNCTIONS</b>	System and cable protection

### SPECIAL FEATURES

- For AC-3 rated operational current with NZM4 the following applies:  
400 V: max. 650 kW;  
690 V: max. 600 kW (switching capacity, rated making and breaking capacity)
- Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity  $I_{cn}$ )
- R.m.s. value measurement and "thermal memory"
- Rated current = rated uninterrupted current: 800 A

---

**INSULATING MATERIAL**

---

**10.10 TEMPERATURE RISE**

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

**10.11 SHORT-CIRCUIT RATING**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC COMPATIBILITY**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

---

**Do pobrania****CHARACTERISTIC CURVE**

[eaton-circuit-breaker-nzm-mccb-characteristic-curve-047.eps](#)

**DEKLARACJE ZGODNOŚCI**

[eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250346en.pdf](#)

**INSTRUKCJE MONTAŻU**

[eaton-circuit-breaker-basic-unit-lzm4-il01210018z.pdf](#)

**MODELE MCAD**

[DA-CD-nzm4\\_3p](#)  
[DA-CS-nzm4\\_3p](#)

**RYSUNKI**

[eaton-circuit-breaker-nzm-mccb-dimensions-022.eps](#)  
[eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-003.eps](#)

---

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATA:**

---



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Irelandia  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Wszelkie prawa zastrzeżone.