

Eaton 185177



Zdjęcie jest reprezentatywne



Eaton Moeller® series C22 Emergency stop/emergency switching off pushbutton, Mushroom-shaped, 38 mm, Turn-to-release function, 2 NC, Cable (black) with non-terminated end, 4 pole, 3.5 m

General specifications

PRODUCT NAME	Eaton Moeller® series C22 Emergency stop/emergency switching off pushbutton
CATALOG NUMBER	185177
EAN	4015081806621
PRODUCT LENGTH/DEPTH	3597 mm
PRODUCT HEIGHT	38 mm
PRODUCT WIDTH	38 mm
PRODUCT WEIGHT	0.151 kg
CERTIFICATIONS	IEC/EN 60947-5-5 CE UL CSA VDE 0660 CSA Class No.: 321103 CSA File No.: 165628 IEC/EN 60947-5-1 UL 508 CSA-C22.2 No. 14-10 CSA-C22.2 No. 94-91 CSA-C22.2 No. 94.2-07 CE marking UL File No.: E340491
CATALOG NOTES	Contacts with safety function, by positive opening to IEC/EN 60947-5-1
MODEL CODE	C22-PVT-K02-P65

Cechy i funkcje

BASE COLOR	Yellow
DESIGN	Mushroom-shaped Classical
FEATURES	Tamper-proof (according to ISO 13850, EN 418) Positive opening
ILLUMINATION	Non-illuminated
UNLOCKING METHOD	Turn-release
UNLOCKING METHOD	Turn-release

Klimatyczne warunki otoczenia

AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MIN	30 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Parametry ogólne

CABLE LENGTH	3.5 m
CABLE MATERIAL	PUR
CONNECTION TO SMARTWIRE-DT	No
CONNECTION TYPE	Cable (black) with non- terminated end, 4 pole
DEGREE OF PROTECTION	NEMA 4X, 13 IP67/IP69K
MOUNTING METHOD	Built-in
MOUNTING POSITION	As required
OPENING DIAMETER	22.5 mm
OPERATING FREQUENCY	300 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	RMQ compact solution
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	800 V AC
SHOCK RESISTANCE	30 g, Mechanical, Shock duration 11 ms
TIGHTENING TORQUE	2 Nm, Threaded ring
TYPE	Controlled stop pushbutton/emergency- stop button

Parametry elektryczne

RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	1 kA
RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	3 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 24 V	4 A
SHORT-CIRCUIT PROTECTION RATING	Max. 4 A gG/gL, Fuse, Contacts
SHORT-CIRCUIT PROTECTION RATING	Max. 4 A gG/gL, Fuse, Contacts

Siłownik

ACTUATING FORCE 50 N

ACTUATOR COLOR Red

ACTUATOR DIAMETER 38 mm

ACTUATOR FUNCTION Turn-to-release

**ACTUATOR TRAVEL AND
ACTUATION FORCE (DIN
EN 60947-5-1)** 4.65 mm

KNOB TRAVEL 5.7 mm

Styki

**CONTROL CIRCUIT
RELIABILITY** 1 failure per 900,000
switching operations
statistically determined, at
17 V DC/7 mA: N/C
contact)

**FORCE FOR POSITIVE
OPENING - MIN** 30 N

**NUMBER OF CONTACTS
(NORMALLY CLOSED
CONTACTS)** 2

**NUMBER OF CONTACTS
(NORMALLY OPEN
CONTACTS)** 0

Do pobrania

**CONTROL TRAVEL
DIAGRAM** [eaton-operating-adapter-
key-operated-actuator-
contact-travel-diagram.eps](#)

DEKLARACJE ZGODNOŚCI [eaton-emergency-stop-
emergency-switching-off-
pushbutton-declaration-
of-conformity-
uk251029en.pdf](#)
[eaton-emergency-stop-
emergency-switching-off-
pushbutton-declaration-
of-conformity-
eu250546en.pdf](#)

INFORMACJE HANDLOWE [eaton-rmq-c22-compact-
pilot-device-flyer-
fl047013en-en-us.pdf](#)

INSTRUKCJE MONTAŻU [IL047010ZU.pdf](#)

MODELE ECAD [DA-CE-ETN.C22-PVT-K02-
P65](#)

MODELE MCAD [DA-CD-
c22_pvt_open_cable](#)
[DA-CS-c22_pvt_open_cable](#)

RYSUNKI [eaton-operating-c22-
dimensions-002.eps](#)
[eaton-operating-3d-
drawing-007.eps](#)

SCHEMATY POŁĄCZEŃ [eaton-operating-c22-
pushbutton-wiring-
diagram-004.eps](#)

ULOTKI [eaton-rmq-titan-selection-
aid-brochure-fl047002-en-
us.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2025 Eaton. Wszelkie prawa zastrzeżone.

Follow us on social media to get the latest product and support information.

