



SIMATIC ET 200AL, DI 8x 24 V DC, 8XM8, Degree of protection IP67

General information	
Product type designation	DI 8x24VDC
HW functional status	FS03
Firmware version	V1.0.x
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version STEP 7 configurable/integrated from version PROFIBUS from GSD version/GSD revision PROFINET from GSD version/GSD revision 	STEP 7 V13 SP1 or higher From V5.5 SP4 Hotfix 3 GSD as of Revision 5 GSDML V2.3.1
Supply voltage	
power supply according to NEC Class 2 required	No
Load voltage 1L+	
<ul style="list-style-type: none"> Rated value (DC) permissible range, lower limit (DC) permissible range, upper limit (DC) Reverse polarity protection 	24 V 20.4 V 28.8 V Yes; Against destruction; encoder power supply outputs applied with reversed polarity
Input current	
Current consumption (rated value)	25 mA; without load
from load voltage 1L+ (unswitched voltage)	4 A; Maximum value
from load voltage 2L+, max.	4 A; Maximum value
Encoder supply	
Number of outputs	8
24 V encoder supply	
<ul style="list-style-type: none"> Short-circuit protection Output current, max. 	Yes; per module, electronic 0.7 A; Total current of all encoders
Power loss	
Power loss, typ.	1.9 W
Digital inputs	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 55 °C, max.	8
Input voltage	
<ul style="list-style-type: none"> Rated value (DC) for signal "0" 	24 V -30 to +5 V

<ul style="list-style-type: none"> • for signal "1" 	+11 to +30V
Input current	
<ul style="list-style-type: none"> • for signal "1", typ. 	3.2 mA
Input delay (for rated value of input voltage)	
for standard inputs	
<ul style="list-style-type: none"> — at "0" to "1", min. 	1.2 ms
<ul style="list-style-type: none"> — at "0" to "1", max. 	4.8 ms
<ul style="list-style-type: none"> — at "1" to "0", min. 	1.2 ms
<ul style="list-style-type: none"> — at "1" to "0", max. 	4.8 ms
Cable length	
<ul style="list-style-type: none"> • unshielded, max. 	30 m
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor 	Yes
<ul style="list-style-type: none"> — permissible quiescent current (2-wire sensor), max. 	1.5 mA
Interrupts/diagnostics/status information	
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes; Parameterizable
Diagnoses	
<ul style="list-style-type: none"> • Short-circuit 	Yes; Sensor supply to M; module by module
Diagnostics indication LED	
<ul style="list-style-type: none"> • Channel status display 	Yes; green LED
<ul style="list-style-type: none"> • for module diagnostics 	Yes; green/red LED
Potential separation	
between the load voltages	Yes
Potential separation channels	
<ul style="list-style-type: none"> • between the channels 	No
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
<ul style="list-style-type: none"> • between the channels and the power supply of the electronics 	No
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP65/67
Standards, approvals, certificates	
Suitable for safety-related tripping of standard modules	Yes; From FS01
Highest safety class achievable for safety-related tripping of standard modules	
<ul style="list-style-type: none"> • Performance level according to ISO 13849-1 	PL d
<ul style="list-style-type: none"> • Category according to ISO 13849-1 	Cat. 3
<ul style="list-style-type: none"> • SIL acc. to IEC 62061 	SIL 2
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. 	-30 °C
<ul style="list-style-type: none"> • max. 	55 °C
connection method / header	
Design of electrical connection for the inputs and outputs	M8, 3-pole
Design of electrical connection for supply voltage	M8, 4-pole
ET-Connection	
<ul style="list-style-type: none"> • ET-Connection 	M8, 4-pin, shielded
Dimensions	
Width	30 mm
Height	159 mm
Depth	40 mm
Weights	
Weight, approx.	145 g
last modified:	3/7/2022 