



SIMATIC ET200PRO PS/3AC/DC24V/8A/IP67

SIMATIC ET200pro PS Regulated power supply in protection type IP67 input: 3 AC 400-480 V output: 24 V/8 A DC

input

type of the power supply network	3-phase AC
supply voltage at AC minimum rated value	400 ... 480 V
supply voltage at AC maximum rated value	
supply voltage at AC initial value	340 ... 550 V
supply voltage at AC full-scale value	
supply voltage at AC	320 ... 340 V for max. 1 min
wide range input	Yes
overvoltage overload capability	Implemented internally with varistors
buffering time for rated value of the output current in the event of power failure minimum	15 ms
operating condition of the mains buffering	at Vin = 400 V
line frequency	50/60 Hz
line frequency initial value	45 ... 66 Hz
line frequency full-scale value	
input current	
• at rated input voltage 400 V	0.5 A
current limitation of inrush current at 25 °C maximum	40 A
I _{2t} value maximum	3.5 A ² ·s
fuse protection type	T 4 A
fuse protection type in the feeder	Required: Circuit breaker 3RV2011-1DA10 or 3RV2711-1DD10 (UL 489)

output

voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
• at output 1 at DC rated value	24 V
output voltage adjustable	No; -
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.5 %
• on slow fluctuation of ohm loading	0.5 %
residual ripple	
• maximum	200 mV
voltage peak	
• maximum	250 mV
display version for normal operation	Green LED for 24 V OK
type of signal at output	max. 30 V, 10 mA; Power-Good (High-Pegel 1L+ for Vout in range 21.3 ... 29 V); Overtemperature warning at least 30 s before switch-off (high level 1L+ when the max. internal temperature is exceeded)
behavior of the output voltage when switching on	Overshoot of Vout < 2 %

response delay maximum	1.5 s
voltage increase time of the output voltage	
• typical	40 ms
output current	
• rated value	8 A
• rated range	0 ... 8 A
supplied active power typical	192 W
short-term overload current	
• on short-circuiting during the start-up typical	50 A
• at short-circuit during operation typical	50 A
duration of overloading capability for excess current	
• on short-circuiting during the start-up	100 ms
• at short-circuit during operation	100 ms
bridging of equipment	No
efficiency in percent	88 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	25 W
closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.5 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	1 %
setting time	
• maximum	2 ms
protection and monitoring	
design of the overvoltage protection	< 33 V
property of the output short-circuit proof	Yes
design of short-circuit protection	Electronic shutdown, automatic restart
• typical	9.4 A
enduring short circuit current RMS value	
• maximum	10 A
safety	
galvanic isolation between input and output	Yes
galvanic isolation	Protective extra low output voltage Vout according to EN 60950-1 and EN 50178
operating resource protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.4 mA
protection class IP	IP67, enclosure type 5 indoor
standard	
• for emitted interference	EN 55022 Class A
• for mains harmonics limitation	-
• for interference immunity	EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	
• CE marking	Yes
• UL approval	Yes; UL-Listed (UL 508) according to NFPA compatibility (National Fire Protection Association), see operating instructions
• CSA approval	No; -
• EAC approval	Yes
• NEC Class 2	No
type of certification	
• CB-certificate	Yes
MTBF at 40 °C	196 354 h
standards, specifications, approvals hazardous environments	
certificate of suitability	
• IECEx	No
• ATEX	No
• ULhazloc approval	No
• cCSAus, Class 1, Division 2	No

• FM registration	No																								
standards, specifications, approvals marine classification																									
shipbuilding approval	No																								
Marine classification association																									
• American Bureau of Shipping Europe Ltd. (ABS)	No																								
• French marine classification society (BV)	No																								
• Det Norske Veritas (DNV)	No																								
• Lloyds Register of Shipping (LRS)	No																								
ambient conditions																									
ambient temperature																									
• during operation	-25 ... +55 °C; with natural convection																								
• during transport	-40 ... +70 °C																								
• during storage	-40 ... +70 °C																								
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation																								
connection method																									
type of electrical connection	screw-type terminals																								
• at input	L1, L2, L3, PE: Plug connector HAN Q4/2 (counterpart see "Electrical accessories")																								
• at output	L+, M: 2 x 1.5 mm ² each (4-pole cable for +/- with open, labeled ends, 4 x 1.5 mm ²)																								
• for auxiliary contacts	Alarm signals: M12 plug-in connector 5-pin																								
mechanical data																									
width x height x depth of the enclosure	310 x 135 x 90 mm																								
fastening method	Can be mounted onto ET200pro mounting rail																								
• standard rail mounting	No																								
• S7 rail mounting	No																								
• wall mounting	Yes																								
housing can be lined up	No																								
net weight	2.8 kg																								
accessories																									
electrical accessories	Power connector (Input: 3RK1911-2BE30 (6 mm ²)) (Output: 3RK1911-2BF10 (4 mm ²))																								
additional information																									
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)																								
security information																									
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>																								
Classifications																									
	<table border="1"> <thead> <tr> <th></th><th>Version</th><th>Classification</th></tr> </thead> <tbody> <tr> <td>eClass</td><td>12</td><td>27-04-07-01</td></tr> <tr> <td>eClass</td><td>9.1</td><td>27-04-07-01</td></tr> <tr> <td>eClass</td><td>9</td><td>27-04-07-01</td></tr> <tr> <td>eClass</td><td>8</td><td>27-04-90-02</td></tr> <tr> <td>eClass</td><td>7.1</td><td>27-04-90-02</td></tr> <tr> <td>eClass</td><td>6</td><td>27-04-90-02</td></tr> <tr> <td>ETIM</td><td>9</td><td>EC002540</td></tr> </tbody> </table>		Version	Classification	eClass	12	27-04-07-01	eClass	9.1	27-04-07-01	eClass	9	27-04-07-01	eClass	8	27-04-90-02	eClass	7.1	27-04-90-02	eClass	6	27-04-90-02	ETIM	9	EC002540
	Version	Classification																							
eClass	12	27-04-07-01																							
eClass	9.1	27-04-07-01																							
eClass	9	27-04-07-01																							
eClass	8	27-04-90-02																							
eClass	7.1	27-04-90-02																							
eClass	6	27-04-90-02																							
ETIM	9	EC002540																							

ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

General Product Approval

[Miscellaneous](#)[Manufacturer Declaration](#)[Declaration of Conformity](#)

last modified:

3/28/2024