

SIMATIC ET 200SP, BusAdapter BA 2xFC, 2x FastConnect connections for PROFINET



General information

| | |
|--------------------------|---------|
| Product type designation | BA 2xFC |
|--------------------------|---------|

Interfaces

| | |
|-------------------------------|---|
| Number of PROFINET interfaces | 1 |
|-------------------------------|---|

Supports protocol for PROFINET IO

| | |
|--|---|
| • Number of FC (FastConnect) connections | 2 |
|--|---|

Cable length

| | |
|-----------------|-------|
| — Cu conductors | 100 m |
|-----------------|-------|

Ambient conditions

Ambient temperature during operation

| | |
|---------------------------------|--------|
| • horizontal installation, min. | -30 °C |
| • horizontal installation, max. | 60 °C |
| • vertical installation, min. | -30 °C |
| • vertical installation, max. | 50 °C |

Altitude during operation relating to sea level

| | |
|---|--|
| • Installation altitude above sea level, max. | 2 000 m; On request: Installation altitudes greater than 2 000 m |
|---|--|

Dimensions

| | |
|--------|---------|
| Width | 20 mm |
| Height | 69.5 mm |
| Depth | 59 mm |

Weights

| | |
|-----------------------|------------|
| Weight, approx. | 53 g |
| last modified: | 02/13/2020 |