

SIMATIC DP, Interface module IM 151-3 PN HF for ET 200S
 Transmission rate 100 Mbit/s max. 63 I/O modules up to 2 m width
 can be connected; 2x bus connections via RJ45 incl. termination
 module



Figure similar

General information	
Product type designation	IM 151-3 PN HF
Configuration control	
via dataset	Yes
Supply voltage	
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
Input current	
from supply voltage 1L+, max.	200 mA
Power loss	
Power loss, typ.	3.3 W
Address area	
Addressing volume	
• Inputs	256 byte
• Outputs	256 byte

Interfaces

Number of PROFINET interfaces	1
Supports protocol for PROFINET IO	
• Autocrossing	Yes
• automatic detection of transmission rate	Yes
• Transmission rate, max.	100 Mbit/s
• Number of RJ45 ports	2

Protocols

Supports protocol for PROFINET IO	Yes
-----------------------------------	-----

Protocols (Ethernet)

• SNMP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes

PROFINET IO Device

Services

— Isochronous mode	No
— IRT	Yes
— PROFINergy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2

Redundancy mode

• MRP	Yes
-------	-----

Interrupts/diagnostics/status information

Alarms	Yes
--------	-----

Diagnostics function	Yes
----------------------	-----

Diagnostics indication LED

• Bus fault BF (red)	Yes
• Group error SF (red)	Yes
• Monitoring 24 V voltage supply ON (green)	Yes
• Connection to network LINK (green)	Yes

Potential separation

between backplane bus and electronics	No
---------------------------------------	----

between supply voltage and electronics	No
--	----

between Ethernet and electronics	Yes
----------------------------------	-----

Isolation

Isolation tested with	500 V
-----------------------	-------

Standards, approvals, certificates

CE mark	Yes
UL approval	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Dimensions	
Width	60 mm
Height	119.5 mm
Depth	75 mm; with mounting rail
Weights	
Weight, approx.	150 g
last modified:	02/13/2020