

ENSTO

PRODUCT SPECIFICATION

2020-02-24



6438100318314

Pole fuse switch disconnecter

SZ160.3



Code	SZ160.3
GTIN	6438100318314
Name	Pole fuse switch disconnecter Al/Cu 2x(16-120) mm ² , poles 3
Description	These pole fuse switches include separate terminal covers for in-coming and outgoing conductors, thus making installation safer. Connectors included 6 x KG45.5, poles 3.

Vendor

Technical specification

Others

ETIM Class: EC001040

Certificates

Standards: IEC 60947-3

Short-circuit characteristics

Rated conditional short-circuit current: 50 kA

Dimensions

Conductor size Al: 16 ... 120 mm²

Conductor size Cu: 16 ... 120 mm²

Weight: 3,7 kg

Features

Connectors included: 6 x KG45.5

Fuse contact: Not included

Number of poles: 3

Utilization category: AC22B

Ratings

Degree of protection: IP23

Electrical values

Fuse:	160 A
Nominal insulation voltage:	1000 V
Nominal voltage (Un):	≥ 0,415 kV
Rated values:	160 A, 415 V

ETIM 7

Etim

Cable entry:	Side
Conditioned rated short-circuit current Iq:	50 kA
Equipped with connectors:	True
Max. rated operation voltage Ue AC:	415 V
Number of poles:	3
Rated permanent current Iu:	160 A
Suitable for fuses:	NH00
Type of control element:	Long turning handle
Type of electrical connection of main circuit:	Cable clamp

Packaging

Pallet package

Unit:	PCE
Package size:	52
Depth:	1200 mm
Width:	800 mm
Height:	1070 mm

Default package

Unit:	PCE
Package size:	1
Depth:	285 mm
Width:	285 mm
Height:	180 mm
Volume:	14,6205 l